



FOR FIRE  
SPRINKLER  
SYSTEMS

**MATERIALS OF  
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40  
HOSE & BRAID - STAINLESS STEEL - 300 SERIES  
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	2" (50mm)	VLUG480200	+/- 24"	69.125"	30.125"	300	20	
	2.5" (65mm)	VLUG480250	+/- 24"	79.375"	34.75"	300	29	
	3" (80mm)	VLUG480300	+/- 24"	83.875"	36.875"	300	37	
	4" (100mm)	VLUG480400	+/- 24"	93.875"	41.125"	175	56	
	5" (125mm)	VLUG480500	+/- 24"	102.625"	44.875"	175	85	
	6" (150mm)	VLUG480600	+/- 24"	112.125"	48.875"	175	124	
	8" (200mm)	VLUG480800	+/- 24"	126.625"	53.625"	175	249	

SUITABLE FOR USE IN DRY PIPE SYSTEMS  
FOR TEMPERATURES TO -40°F.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
<b>METRAFLEX FIREVOOP™</b> GROOVED ENDS, +/- 24" MOVEMENT	
DRAWN BY: <b>DKISH</b>	DATE: <b>8/24/2015</b>
APPROVED: <b>ZB</b>	DATE: <b>8/24/2015</b>
SCALE: N/A	DRAWING NUMBER: <b>VLUG48NEW</b>