



FOR FIRE
SPRINKLER
SYSTEMS

**MATERIALS OF
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40
HOSE & BRAID - STAINLESS STEEL - 300 SERIES
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	2" (50mm)	VLUG80200	+/- 4"	37.25"	14.25"	300	12	
	2.5" (65mm)	VLUG80250	+/- 4"	43.5"	16.875"	300	19	
	3" (80mm)	VLUG80300	+/- 4"	46.5"	18.125"	300	24	
	4" (100mm)	VLUG80400	+/- 4"	52.875"	20.75"	175	38	
	5" (125mm)	VLUG80500	+/- 4"	59"	23.125"	175	59	
	6" (150mm)	VLUG80600	+/- 4"	65.5"	25.625"	175	88	
	8" (200mm)	VLUG80800	+/- 4"	77.625"	29.125"	175	171	

SUITABLE FOR USE IN DRY PIPE SYSTEMS
FOR TEMPERATURES TO -40°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX FIREVOOP™ GROOVED ENDS, +/- 4" MOVEMENT	
DRAWN BY: DKISH	DATE: 8/24/2015
APPROVED: ZB	DATE: 8/24/2015
SCALE: N/A	DRAWING NUMBER: VLUG8NEW