



FOR FIRE
SPRINKLER
SYSTEMS

**MATERIALS OF
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40
HOSE & BRAID - STAINLESS STEEL - 300 SERIES
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	2" (50mm)	VLUG160200	+/- 8"	46"	18.5"	300	14	
	2.5" (65mm)	VLUG160250	+/- 8"	53.375"	21.75"	300	22	
	3" (80mm)	VLUG160300	+/- 8"	56.75"	23.25"	300	28	
	4" (100mm)	VLUG160400	+/- 8"	64.25"	26.375"	175	43	
	5" (125mm)	VLUG160500	+/- 8"	71.125"	29.125"	175	66	
	6" (150mm)	VLUG160600	+/- 8"	78.5"	32.125"	175	98	
	8" (200mm)	VLUG160800	+/- 8"	91.375"	36"	175	193	

SUITABLE FOR USE IN DRY PIPE SYSTEMS
FOR TEMPERATURES TO -40°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX FIREVOOP™ GROOVED ENDS, +/- 8" MOVEMENT	
DRAWN BY: DKISH	DATE: 8/24/2015
APPROVED: ZB	DATE: 8/24/2015
SCALE: N/A	DRAWING NUMBER: VLUG16NEW