



FOR FIRE  
SPRINKLER  
SYSTEMS

**MATERIALS OF  
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40  
HOSE & BRAID - STAINLESS STEEL - 300 SERIES  
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	0.5" (15mm)	VLUT80050	+/- 4"	25"	8.75"	300	2	
	0.75" (20mm)	VLUT80075	+/- 4"	27.75"	10"	300	3	
	1" (25mm)	VLUT80100	+/- 4"	29"	10.75"	300	5	
	1.25" (32mm)	VLUT80125	+/- 4"	31.25"	11.625"	300	6	
	1.5" (40mm)	VLUT80150	+/- 4"	33.375"	12.5"	300	8	
	2" (50mm)	VLUT80200	+/- 4"	37.25"	14.25"	300	12	

SUITABLE FOR USE IN DRY PIPE SYSTEMS  
FOR TEMPERATURES TO -40°F.

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
<b>METRAFLEX FIREVOOP™</b> THREAD ENDS, +/- 4" MOVEMENT	
DRAWN BY: <b>DKISH</b>	DATE: <b>8/24/2015</b>
APPROVED: <b>ZB</b>	DATE: <b>8/24/2015</b>
SCALE: <b>N/A</b>	DRAWING NUMBER: <b>VLUT8NEW</b>