



FOR FIRE
SPRINKLER
SYSTEMS

**MATERIALS OF
CONSTRUCTION**

END FITTINGS - CARBON STEEL - SCH 40
HOSE & BRAID - STAINLESS STEEL - 300 SERIES
ELBOWS - CARBON STEEL - SCH 40

NOTE: FIREVOOP INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	0.5" (15mm)	VLUT160050	+/- 8"	30.875"	11.625"	300	3	
	0.75" (20mm)	VLUT160075	+/- 8"	34.375"	13.375"	300	4	
	1" (25mm)	VLUT160100	+/- 8"	36"	14.125"	300	5	
	1.25" (32mm)	VLUT160125	+/- 8"	38.625"	15.375"	300	7	
	1.5" (40mm)	VLUT160150	+/- 8"	41.125"	16.5"	300	9	
	2" (50mm)	VLUT160200	+/- 8"	46"	18.5"	300	14	

SUITABLE FOR USE IN DRY PIPE SYSTEMS
FOR TEMPERATURES TO -40°F.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX FIREVOOP™ THREAD ENDS, +/- 8" MOVEMENT	
DRAWN BY: DKISH	DATE: 8/24/2015
APPROVED: ZB	DATE: 8/24/2015
SCALE: N/A	DRAWING NUMBER: VLUT16NEW