

MATERIALS OF CONSTRUCTION
 END FITTINGS - CARBON STEEL - SCH 40
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	0.5" (15mm)	VLT40050	+/- 2"	21.125"	6.75"	1075	2	
	0.75" (20mm)	VLT40075	+/- 2"	23.25"	7.75"	792	3	
	1" (25mm)	VLT40100	+/- 2"	24.375"	8.375"	571	4	
	1.25" (32mm)	VLT40125	+/- 2"	26.125"	9.125"	531	5	
	1.5" (40mm)	VLT40150	+/- 2"	28"	9.875"	472	6	
	2" (50mm)	VLT40200	+/- 2"	31.375"	11.25"	500	9	
	2.5" (65mm)	VLT40250	+/- 2"	36.625"	13.375"	387	15	
	3" (80mm)	VLT40300	+/- 2"	39.25"	14.5"	288	20	
	4" (100mm)	VLT40400	+/- 2"	47"	16.75"	232	32	


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX V-LOOP THREAD ENDS, +/- 2" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/29/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLT4