



This is a flexible member and adjacent pipe must be properly anchored and guided. Coupling to be slipped over pipe to a depth of 2". Torque bolt to 225 inch-pounds.

Qty.	Pipe Size (in)	Size I.D. (in)	Face To Face (in)	Pressure (PSI)	Vacuum (in Hg)	Comp. (in)	Elong. (in)	Angular (Degrees)	Weight (Lbs)
	2	2-3/8	7	75	20	1	1/2	10	1.6
	2-1/2	2-7/8	7	75	20	1	1/2	10	1.8
	3	3-1/2	7	75	20	1	1/2	10	2.0
	3-1/2	4	7	75	20	1	1/2	10	2.2
	4	4-1/2	7	75	20	1	1/2	10	2.4
	4-1/2	5	7	75	20	1	1/2	10	2.7
	5	5-5/8	7	75	20	1	1/2	10	2.9
	6	6-5/8	7	75	20	1	1/2	10	3.4
	8	8-5/8	7	75	20	1	1/2	10	4.3
	10	10-3/4	7	75	20	1	1/2	10	5.1
	12	12-3/4	7	75	20	1	1/2	10	6.7

MAXIMUM WORKING TEMPERATURE 225°F

NOTES

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
STYLE 201 FLEXIBLE COUPLING	
DRAWN BY: DKISH	DATE: 11/4/2014
APPROVED: JC	DATE: 11/4/2014
SCALE: NONE	DRAWING NUMBER: 201