



FOR TEMP. ABOVE 70° F.	
TEMP. °F	FACTOR
70	1.00
200	.92
300	.86
400	.82
500	.77
600	.73

QTY	PIPE SIZE	A	PRESS. @ 70° F*	NOTES
	2"	12"	455	
	2.5"	12"	345	
	3"	14"	289	
	4"	16"	300	
	5"	18"	220	
	6"	20"	200	
	8"	22"	190	
	10"	24"	150	
	12"	26"	125	
	14"	28"	105	

\*FOR SAFE WORKING PRESSURE ABOVE 70° F. MULTIPLY PRESSURE SHOWN AT 70° F. TIMES CORRECTION FACTOR OF REQUIRED TEMP.

MAX. PERMANENT OFFSET FROM  $\text{C}$  1"

MAX. INTERMITTENT OFFSET FROM  $\text{C}$  3/4"

CUSTOMER \_\_\_\_\_

PROJECT \_\_\_\_\_

ENGINEER \_\_\_\_\_

ARCHITECT \_\_\_\_\_

PRO. OR P.O. NO. \_\_\_\_\_



DESCRIPTION:

**MODEL MLP**  
**STAINLESS STEEL PUMP CONNECTOR**

DRAWING BY: JT

DATE: 8/6/10

DRAWING NO. 150 SF—MLP R1