



FOR TEMP. ABOVE 70° F.	
TEMP. °F.	FACTOR
70	1.00
200	.92
300	.86
400	.82
500	.77
600	.73

* FOR SAFE WORKING PRESSURE ABOVE 70° F. MULTIPLY PRESSURE SHOWN AT 70° F. TIMES CORRECTION FACTOR OF REQUIRED TEMP.

QTY.	PIPE SIZE	A	PRESS. @ 70° F.*	NOTES
	2.5"	10-1/4"	345	
	3"	10-5/8"	289	
	4"	11-3/4"	300	
	5"	13-5/8"	220	
	6"	14-1/8"	200	
	8"	15-3/8"	190	
	10"	17-3/4"	150	
	12"	18-3/8"	125	
	14"	20"	105	

MAX. PERMANENT OFFSET FROM C 3/4"
 MAX. INTERMITTENT OFFSET FROM C 3/8"

CUSTOMER _____
 PROJECT _____
 ENGINEER _____
 ARCHITECT _____
 PRO. OR P.O. NO _____



DESCRIPTION:

MODEL SLP
STAINLESS STEEL PUMP CONNECTOR

DRAWN BY: J R	DATE: 12-1-95	DRAWING NO: 150 SF-SLP
-------------------------	-------------------------	----------------------------------