

FOR TEMP. ABOVE 70° F.	
FACTOR	
TEMP. ° F	S.S.
70	1.00
200	.92
300	.86
400	.82
500	.77
600	.73


QTY.	PIPE SIZE	A	PRESSURE (PSI) @ 70° F.*	NOTES
	3/8"	6"	1900	
	1/2"	6-1/2"	1300	
	3/4"	7"	750	
	1"	8"	605	
	1-1/4"	8-1/2"	570	
	1-1/2"	9"	525	
	2"	10-1/2"	455	

MAX. INTERMITTENT OFFSET FROM $\pm 1/8"$

MATERIAL SPECIFICATIONS

PIPE ENDS : CARBON STEEL SCH'D. 40 IPS
 HOSE: STAINLESS STEEL
 BRAID: STAINLESS STEEL

* FOR SAFE WORKING PRESSURE ABOVE 70° F. MULTIPLY PRESSURE SHOWN AT 70° F. TIMES CORRECTION FACTOR OF REQUIRED TEMP.

CUSTOMER _____ PROJECT _____ ENGINEER _____ ARCHITECT _____ PRO. OR P.O. NO _____			
	DESCRIPTION: MODEL SSTT SHORT LENGTH METAL CONNECTOR, THREADED		
	DRAWN BY: J.O.	DATE: 8/00	DRAWING NO: SSTT