

C (CLEARANCE TO REMOVE STRAINER FROM BELOW)
*IF THERE IS NOT ENOUGH CLEARANCE BELOW STRAINER,
PRODUCT CAN BE ROTATED 90° AXIALLY TO PROVIDE CLEARANCE
OR FOR STEAM APPLICATION TO MINIMIZE CONDENSATE COLLECTION

STANDARD SCREENS

SERVICE	SIZE	PERF		
LIQUID	10" - 24"	.125"		
STEAM	10" - 24"	.062"		

MATERIALS OF CONSTRUCTION

BODY, FLANGES, COVER PLATE - CAST IRON (10"-18")/DUCTILE IRON (20"-24") SCREEN - 304 STAINLESS STEEL O-RING GASKET - VITON

OPERATING TEMPERATURE/PRESSURE

WATER, OIL, GAS......175 PSI @ 150°F STEAM.....125 PSI @ 350°F

QTY	PART NUMBER	PIPE SIZE		٨	В	С	#Cv	SCREEN AREA	PORT SIZE (NPT)		BLOWOFF	TAP SIZE	TAP	WEIGHT
		INCH	MM	A	D		(GPM)	(in²)	1 & 2	3	SIZE (NPT)	(UNC)	DEPTH	(LBS)
	LPD1000	10"	250	27"	16-5/8"	37-7/8"	2424	745.2	3/8"	1''	2"	7/8"-9	1-1/8"	464
	LPD1200	12"	300	29-7/8"	19-3/4"	43-5/8"	3200	1035.1	3/8"	1"	2"	7/8"-9	1-1/8"	565
	LPD1400	14"	350	33-1/4"	22-1/4"	49-1/2"	4385	1276.0	3/8"	1"	2"	1"-8	1-1/4"	900
	LPD1600	16"	400	38-3/4"	25-5/8"	58-1/4"	6064	1750.0	3/8"	1''	2"	1"-8	1-1/4"	1300
	LPD1800	18"	462	43-1/8"	27-1/8"	62-1/4"	7535	2083.0	3/8"	1"	2"	1-1/8"-7	1-1/4"	1700
	LPD2000	20"	508	49-1/2"	30-1/4"	72"	8983	2674.0	3/8"	1"	2"	1-1/8"-7	1-1/4"	2100
	LPD2400	24"	610	55-13/16"	35-7/8"	80"	11331	3517.0	3/8"	1"	2"	1-1/8"-7	1-1/4"	3500

 $^{\#}$ CV is the flow rate in Gallons of 60°F water that will pass through the strainer in 1 minute at a 1 psi pressure drop.

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER:	
PROJECT:	
FNGINFFR:	

5	REVISED Cv	11/26/2025
REV. 4	CV AND SCR. AREA FOR 14" - 24"	DATE: 02/14/2025



SCALE:

2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM

MODEL LPD

LOW PRESSURE DROP 125# FLANGED STRAINER

DRAWN BY: JULIANH	DATE: 10/04/2024
APPROVED:	DATE:

E: DRAWING NUMBER: LPD-10-24-5