

MODEL MNLC300 - SIZES 10" THROUGH 24" LOW CORRUGATION EXPANSION JOINT, 300# CLASS






DESIGN DATA

WORKING PRESSURE: 300 PSI WORKING TEMPERATURE: 800°F

TEST PRESSURE: 450 PSI

MATERIALS OF CONSTRUCTION

BELLOWS: 316 STAINLESS STEEL 300# FLANGES: CARBON STEEL WELD ENDS: CARBON STEEL SCH STD



CUSTOM SIZES ARE AVAILABLE.
CONTACT METRAFLEX FOR DETAILS.
WHEN ORDERING, SPECIFY MOVEMENT.

DOUBLE WITH ANCHOR BASE (CONTACT FACTORY)

| | | | | | | | • | | |
|-----|--------------|-----------------|----------------|---------------|----------|-----------|---------|---------------------|--------------|
| QTY | PIPE SIZE | SHORT / LONG | AXIAL COMP. | FLANGED ENDS | | WELD ENDS | | EFFECTIVE | SPRING |
| | | | | OAL | WT | OAL | WT | AREA | RATE |
| | 10" | S | 1" | 9-3/8" | 168 LBS | 12-1/8" | 27 LBS | 104 in ² | 2996 lbs/in |
| | | L | 2-1/2" | 14-3/8" | 179 LBS | 17-1/4" | 35 LBS | | 1226 lbs/in |
| | 12" | S | 1" | 9-3/4" | 210 LBS | 12-1/2" | 39 LBS | 146 in² | 4586 lbs/in |
| | | L | 2-1/4" | 13-1/2" | 231 LBS | 16-1/4" | 46 LBS | | 2293 lbs/in |
| | 14" | S | 1" | 10-3/8" | 386 LBS | 14-1/8" | 132 LBS | 183 in² | 5120 lbs/in |
| | | L | 2" | 15" | 414 LBS | 18-3/4" | 160 LBS | | 2560 lbs/in |
| | 16" | S | 1-1/2" | 11-1/4" | 440 LBS | 15" | 92 LBS | 237 in² | 4240 lbs/in |
| | | L | 3" | 16-3/4" | 470 LBS | 20-1/2" | 122 LBS | | 2120 lbs/in |
| | 18" | S | 1-1/2" | 11-1/2" | 564 LBS | 15" | 99 LBS | 298 in² | 6500 lbs/in |
| | | L | 3" | 1 <i>7</i> '' | 598 LBS | 20-1/2" | 131 LBS | | 3240 lbs/in |
| | 20" | S | 1-1/2" | 13-3/8" | 710 LBS | 15" | 113 LBS | 362 in ² | 7130 lbs/in |
| | | L | 3" | 18-7/8" | 750 LBS | 20-1/2" | 173 LBS | | 3600 lbs/in |
| | 22" | S | 1-1/2" | 14" | 830 LBS | 15" | 152 LBS | 434 in² | 11800 lbs/in |
| | | L | 3" | 19-1/2" | 875 LBS | 20-1/2" | 202 LBS | | 5900 lbs/in |
| | 0.4" | S | 1-1/2" | 14-1/4" | 1030 LBS | 15" | 180 LBS | 512 in² | 12300 lbs/in |
| | 24" | L | 3" | 19-3/4" | 1070 LBS | 20-1/2" | 220 LBS | | 6200 lbs/in |

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

| CUSTOMER: | _ |
|-----------|---|
| PROJECT: | _ |
| ENGINEER: | _ |

| REV. | | DATE |
|--------------------|-------|---|
| Me for pipes in | rafle | 2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM |

MODEL MNLC

LOW CORRUGATION EXPANSION JOINT, 300# CLASS

| DRAWN BY: DKISH | DATE: 2/1/2018 |
|------------------------|-----------------------|
| APPROVED: JC | DATE: 2/1/2018 |

SCALE: DRAWING NUMBER: MNLC300-10TO24-1