



MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	2" (50mm)	VLG40200	+/- 2"	31.375"	11.25"	516	9	
	2.5" (65mm)	VLG40250	+/- 2"	36.625"	13.375"	387	15	
	3" (80mm)	VLG40300	+/- 2"	39.25"	14.5"	316	20	
	4" (100mm)	VLG40400	+/- 2"	45"	16.75"	232	32	
	5" (125mm)	VLG40500	+/- 2"	50.5"	18.875"	191	51	
	6" (150mm)	VLG40600	+/- 2"	56.375"	21"	165	76	
	8" (200mm)	VLG40800	+/- 2"	68.125"	24.375"	234	144	
	10" (250mm)	VLG41000	+/- 2"	79.25"	28.5"	230	238	
	12" (300mm)	VLG41200	+/- 2"	90.25"	32.5"	161	337	

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM	
METRAFLEX V-LOOP GROOVED ENDS, +/- 2" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/31/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLG4