

MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	2" (50mm)	VLF40200	+/- 2"	25.875"	11.25"	516	15	
	2.5" (65mm)	VLF40250	+/- 2"	31.125"	13.375"	387	23	
	3" (80mm)	VLF40300	+/- 2"	33.75"	14.5"	316	28	
	4" (100mm)	VLF40400	+/- 2"	39.5"	16.75"	232	43	
	5" (125mm)	VLF40500	+/- 2"	45"	18.875"	191	64	
	6" (150mm)	VLF40600	+/- 2"	50.875"	21"	165	89	
	8" (200mm)	VLF40800	+/- 2"	60.625"	24.375"	234	175	
	10" (250mm)	VLF41000	+/- 2"	71.75"	28.5"	230	271	
	12" (300mm)	VLF41200	+/- 2"	82.75"	32.5"	161	392	


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM	
METRAFLEX V-LOOP FLANGED ENDS, +/- 2" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/31/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLF4