

MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	2" (50mm)	VLF60200	+/- 3"	29"	12.875"	516	16	
	2.5" (65mm)	VLF60250	+/- 3"	34.75"	15.25"	387	24	
	3" (80mm)	VLF60300	+/- 3"	37.625"	16.5"	316	29	
	4" (100mm)	VLF60400	+/- 3"	43.75"	18.875"	232	44	
	5" (125mm)	VLF60500	+/- 3"	49.625"	21.125"	191	66	
	6" (150mm)	VLF60600	+/- 3"	55.875"	23.5"	165	92	
	8" (200mm)	VLF60800	+/- 3"	65.75"	27"	234	181	
	10" (250mm)	VLF61000	+/- 3"	77.625"	31.5"	230	280	
	12" (300mm)	VLF61200	+/- 3"	89.125"	35.75"	161	403	


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM	
METRAFLEX V-LOOP FLANGED ENDS, +/- 3" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/31/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLF6