



MATERIALS OF CONSTRUCTION
 END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI	WT (LBS)	PROJECT INFO
	2" (50mm)	VLG60200	+/- 3"	34.5"	12.875"	516	10	
	2.5" (65mm)	VLG60250	+/- 3"	40.25"	15.25"	387	16	
	3" (80mm)	VLG60300	+/- 3"	43.125"	16.5"	316	21	
	4" (100mm)	VLG60400	+/- 3"	49.25"	18.875"	232	34	
	5" (125mm)	VLG60500	+/- 3"	55.125"	21.125"	191	53	
	6" (150mm)	VLG60600	+/- 3"	61.375"	23.5"	165	79	
	8" (200mm)	VLG60800	+/- 3"	73.25"	27"	234	150	
	10" (250mm)	VLG61000	+/- 3"	85.125"	31.5"	230	247	
	12" (300mm)	VLG61200	+/- 3"	96.625"	35.75"	161	348	

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM	
METRAFLEX V-LOOP GROOVED ENDS, +/- 3" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/29/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLG6