



MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	2" (50mm)	VLG80200	+/- 4"	37.25"	14.25"	516	10	
	2.5" (65mm)	VLG80250	+/- 4"	43.5"	16.875"	387	16	
	3" (80mm)	VLG80300	+/- 4"	46.5"	18.125"	316	22	
	4" (100mm)	VLG80400	+/- 4"	52.875"	20.75"	232	35	
	5" (125mm)	VLG80500	+/- 4"	59"	23.125"	191	54	
	6" (150mm)	VLG80600	+/- 4"	65.5"	25.625"	165	81	
	8" (200mm)	VLG80800	+/- 4"	77.625"	29.125"	234	155	
	10" (250mm)	VLG81000	+/- 4"	90"	33.875"	230	254	
	12" (300mm)	VLG81200	+/- 4"	102"	38.375"	161	357	

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM	
METRAFLEX V-LOOP GROOVED ENDS, +/- 4" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/29/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLG8