



MATERIALS OF CONSTRUCTION
 END FITTINGS - CARBON STEEL - SCH 40
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	0.5" (15mm)	VLT60050	+/- 3"	23.25"	7.75"	1075	2	
	0.75" (20mm)	VLT60075	+/- 3"	25.75"	9"	792	3	
	1" (25mm)	VLT60100	+/- 3"	26.875"	9.625"	571	4	
	1.25" (32mm)	VLT60125	+/- 3"	28.875"	10.5"	531	5	
	1.5" (40mm)	VLT60150	+/- 3"	30.875"	11.375"	472	7	
	2" (50mm)	VLT60200	+/- 3"	34.5"	12.875"	500	10	
	2.5" (65mm)	VLT60250	+/- 3"	40.25"	15.25"	387	16	
	3" (80mm)	VLT60300	+/- 3"	43.125"	16.5"	288	21	
	4" (100mm)	VLT60400	+/- 3"	51.25"	18.875"	232	34	

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX V-LOOP THREAD ENDS, +/- 3" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/30/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLT6