

MATERIALS OF CONSTRUCTION
 END FITTINGS - CARBON STEEL - SCH 40
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

QTY	SIZE	MODEL	MOVEMENT	A	B	PSI @ 70° F	WT (LBS)	PROJECT INFO
	0.5" (15mm)	VLT80050	+/- 4"	25"	8.75"	1075	2	
	0.75" (20mm)	VLT80075	+/- 4"	27.75"	10"	792	3	
	1" (25mm)	VLT80100	+/- 4"	29"	10.75"	571	4	
	1.25" (32mm)	VLT80125	+/- 4"	31.25"	11.625"	531	6	
	1.5" (40mm)	VLT80150	+/- 4"	33.375"	12.5"	472	7	
	2" (50mm)	VLT80200	+/- 4"	37.25"	14.25"	500	10	
	2.5" (65mm)	VLT80250	+/- 4"	43.5"	16.875"	387	16	
	3" (80mm)	VLT80300	+/- 4"	46.5"	18.125"	288	22	
	4" (100mm)	VLT80400	+/- 4"	54.875"	20.75"	232	35	


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFIRE.COM	
METRAFLEX V-LOOP THREAD ENDS, +/- 4" MOVEMENT	
DRAWN BY: SMARTEN	DATE: 7/29/2015
APPROVED: DKISH	DATE: 8/3/2015
SCALE: NONE	DRAWING NUMBER: VLT8