



NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

ITEM	PART NAME	MATERIAL			
1	BODY	CAST IRON			
2	SCREEN	STAINLESS STEEL			
3	COVER	CAST IRON			
4	BLOWOFF PLUG	CAST IRON			


OPERATING TEMPERATURE & PRESSURE (NON SHOCK)

Steam......250 PSI at 400 °F Water, Oil, Gas......400 PSI at 150 °F

Qty	Part Number	Size I.D. (in)	A (in)	B (in)	Blowoff Size NPT	Weight (Lbs)	Screen Area (in²)	Project Info
	TSC0050	1/2	3-7/16	2-1/2	3/8	1.50	5.4	
	TSC0075	3/4	4	2-3/4	1/2	2.50	8.7	
	TSC0100	1	4-5/8	3-1/4	1/2	4.50	11.9	
	TSC0125	1-1/4	5-3/8	4	3/4	6.50	16.2	
	TSC0150	1-1/2	6	4-1/2	3/4	8.75	23.2	
	TSC0200	2	7-1/2	5-3/8	1	12.50	35.0	
	TSC0250	2-1/2	9	7-3/16	1-1/4	24.00	54.0	
	TSC0300	3	10	7-7/8	1-1/4	30.00	73.0	

STANDARD SCREENS:

SERVICE	SIZES	SCREEN OPENINGS			
LIQUID/	1/4" - 2"	20 MESH			
STEAM	2-1/2" - 3"	.045 PERF			



CUSTOMER:_____

PROJECT:_

ENGINEER:_____