



C (HEIGHT ABOVE FACE WHEN DISCS ARE FULLY OPEN)

MATERIAL

EPOXY COATED

CAST IRON

STAINLESS STEEL

STAINLESS STEEL

STAINLESS STEEL

EPDM

PTFE

NBR

2	3		4)	
5				
-		— A —		

PART NAME

BODY

DISC

SPRING

SHAFT

SEAT

WASHER

SEAL

MAX NON-SHOCK WORKING PSI

SIZE	150°F	200°F	
2" TO 12"	200 PSI	190 PSI	
14" AND UP	150 PSI	135 PSI	

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

Notes:

Valve is designed for liquid service only. Install 5 to 10 pipe diameters downstream from pump discharge or elbows. To avoid turbulence, use with a VANEFLEX connector.

Valve is designed to be mated to ANSI B16.5 steel flanges.

For vertical pipe, install with flow up. For horizontal pipe, install with hinge pin in vertical position.

8 SELSCREW			STAINLESS STEEL							
Qty.	Part	Number	Size I.D. (in)	A (in)	B (in)	C (in)	Cv*	Weight (Lbs)	Bolt Size (in)	Project Info
	CV)	XXK0200	2	4	1-3/4	1/4	48	3	5/8	
	CV)	XXK0250	2-1/2	4-3/4	1-7/8	5/8	99	5	5/8	
	CV)	XXK0300	3	5-1/4	2-1/2	1/2	171	8	5/8	
	CVX	XXK0400	4	6-3/4	2-1/2	1-1/8	290	13	5/8	
	CV)	XXK0500	5	7-5/8	2-3/4	1-3/8	489	16	3/4	
	CV)	XXK0600	6	8-5/8	3	1-5/8	695	20	3/4	
	CV)	XXK0800	8	10-7/8	3-1/2	2-7/8	1789	38	3/4	
	CVX	XXK1000	10	13-1/4	4-1/2	3	2557	57	7/8	
	CV)	XXK1200	12	16	4-1/2	4-5/8	4287	93	7/8	
	CV)	XXK1400	14	17-5/8	5	5	5456	121	1	
	CV)	XXK1600	16	20	5-1/2	5-3/4	7342	165	1	
	CV)	XXK1800	18	21-1/2	6	6-3/8	9532	223	1-1/8	
	CV)	XXK2000	20	23-3/4	6	7-1/8	12000	245	1-1/8	

*Cv is the number of U.S. gallons/minute of 60°F water that will flow through a valve with 1 PSI of pressure drop across the valve.



ITEM

1

2

3

4

5

6

7

0

FOR ADDITIONAL FLOW STRAIGHTENING SEE THE VANEFLEX AT www.metraflex.com/vaneflex

CUSTOMER:_____

PROJECT:

ENGINEER:_____

