


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PRESSURE RATING*	SPRING FORCE
		INCH	MM				
	DLF40200	2"	50	±2"	19-1/2"	500	78
	DLF40250	2-1/2"	65	±2"	23"	387	83
	DLF40300	3"	80	±2"	24-1/2"	288	90
	DLF40400	4"	100	±2"	28"	232	120
	DLF40500	5"	125	±2"	31"	191	186
	DLF40600	6"	150	±2"	34"	165	202
	DLF40800	8"	200	±2"	38-1/2"	212	260
	DLF41000	10"	250	±2"	44"	175	283
	DLF41200	12"	300	±2"	49-1/2"	160	390
	DLF41400	14"	355	±2"	55"	110	706
	DLF41600	16"	400	±2"	58-1/2"	110	900
	DLF41800	18"	455	±2"	63-1/2"	85	1000

\*FOR SAFE WORKING PRESSURE ABOVE 70°F,  
MULTIPLY THE PRESSURE SHOWN AT 70°F  
TIMES THE CORRECTION FACTOR OF THE  
REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

### NSF 372 - LEAD FREE

The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>MODEL DLF4</b> FLANGED DOG LEG, ±2" MOVEMENT	
DRAWN BY: <b>RDAHYA</b>	DATE: <b>11/20/2020</b>
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: <b>DLF4</b>