


| QTY | PART NUMBER | PIPE SIZE | | MOVEMENT | CENTER TO END | PRESSURE RATING* | SPRING FORCE |
|-----|-------------|-----------|-----|----------|---------------|------------------|--------------|
| | | INCH | MM | | | | |
| | DLF80200 | 2" | 50 | ±4" | 26" | 500 | 78 |
| | DLF80250 | 2-1/2" | 65 | ±4" | 30" | 387 | 83 |
| | DLF80300 | 3" | 80 | ±4" | 32" | 288 | 90 |
| | DLF80400 | 4" | 100 | ±4" | 36" | 232 | 120 |
| | DLF80500 | 5" | 125 | ±4" | 39-1/2" | 191 | 186 |
| | DLF80600 | 6" | 150 | ±4" | 43" | 165 | 202 |
| | DLF80800 | 8" | 200 | ±4" | 48" | 212 | 260 |
| | DLF81000 | 10" | 250 | ±4" | 55" | 175 | 283 |
| | DLF81200 | 12" | 300 | ±4" | 61-1/2" | 160 | 390 |
| | DLF81400 | 14" | 355 | ±4" | 67-1/2" | 110 | 706 |
| | DLF81600 | 16" | 400 | ±4" | 72" | 110 | 900 |
| | DLF81800 | 18" | 455 | ±4" | 77" | 85 | 1000 |

*FOR SAFE WORKING PRESSURE ABOVE 70°F,
MULTIPLY THE PRESSURE SHOWN AT 70°F
TIMES THE CORRECTION FACTOR OF THE
REQUIRED TEMPERATURE.

| TEMPERATURE (°F) | FACTOR |
|------------------|--------|
| 70 | 1.0 |
| 200 | 0.91 |
| 300 | 0.85 |
| 400 | 0.78 |
| 500 | 0.77 |
| 600 | 0.76 |

NSF 372 - LEAD FREE

The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

| REV. | DATE |
|---------------------------------------------------------------------------------------------------------|-----------------------------|
|  | |
| 2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM | |
| MODEL DLF8 FLANGED DOG LEG, ±4" MOVEMENT | |
| DRAWN BY: RDAHYA | DATE: 11/20/2020 |
| APPROVED: | DATE: |
| SCALE: N/A | DRAWING NUMBER: DLF8 |