


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PRESSURE RATING*	SPRING FORCE
		INCH	MM				
	DLF80200	2"	50	±4"	26"	500	78
	DLF80250	2-1/2"	65	±4"	30"	387	83
	DLF80300	3"	80	±4"	32"	288	90
	DLF80400	4"	100	±4"	36"	232	120
	DLF80500	5"	125	±4"	39-1/2"	191	186
	DLF80600	6"	150	±4"	43"	165	202
	DLF80800	8"	200	±4"	48"	212	260
	DLF81000	10"	250	±4"	55"	175	283
	DLF81200	12"	300	±4"	61-1/2"	160	390
	DLF81400	14"	355	±4"	67-1/2"	110	706
	DLF81600	16"	400	±4"	72"	110	900
	DLF81800	18"	455	±4"	77"	85	1000

*FOR SAFE WORKING PRESSURE ABOVE 70°F,
MULTIPLY THE PRESSURE SHOWN AT 70°F
TIMES THE CORRECTION FACTOR OF THE
REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL DLF8 FLANGED DOG LEG, ±4" MOVEMENT	
DRAWN BY: RDAHYA	DATE: 11/20/2020
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: DLF8