


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PRESSURE RATING*	SPRING FORCE
		INCH	MM				
	DLG40200	2"	50	±2"	22"	500	78
	DLG40250	2-1/2"	65	±2"	25-1/2"	387	83
	DLG40300	3"	80	±2"	27"	288	90
	DLG40400	4"	100	±2"	30-1/2"	232	120
	DLG40500	5"	125	±2"	33"	191	186
	DLG40600	6"	150	±2"	36-1/2"	165	202
	DLG40800	8"	200	±2"	41-1/2"	212	260
	DLG41000	10"	250	±2"	47"	175	383
	DLG41200	12"	300	±2"	52-1/2"	160	390

\*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

**NSF 372 - LEAD FREE**

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>MODEL DLG4</b> GROOVED DOG LEG, ±2" MOVEMENT	
DRAWN BY: <b>RDAHYA</b>	DATE: <b>11/20/2020</b>
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: <b>DLG4</b>