

QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PRESSURE RATING*	SPRING FORCE		
		INCH	MM				0.1		
	DLG80200	2"	50	±4"	28"	500	78		
	DLG80250	2-1/2"	65	±4"	32-1/2"	387	83		
	DLG80300	3"	80	±4"	34-1/2"	288	90		
	DLG80400	4''	100	±4"	38-1/2"	232	120		
	DLG80500	5"	125	±4"	42"	191	186		
	DLG80600	6"	150	±4"	45-1/2"	165	202		
	DLG80800	8"	200	±4"	51"	212	260		
	DLG81000	10"	250	±4"	58"	175	383		
	DLG81200	12"	300	±4"	64-1/2"	160	390		

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSUURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.



DRAWN BY: RDAHYA DATE: 11/20/2020

APPROVED: DATE:

SCALE: DRAWING NUMBER: DLG8