

QTY	PART NUMBER	PIPE SIZE INCH MM		MOVEMENT	CENTER TO END	PRESSURE RATING*	SPRING FORCE	
			101101					
	DLS40050	1/2"	15	±2"	13"	706	45	
	DLS40075	3/4"	20	±2"	14-1/2"	577	47	
	DLS40100	1"	25	±2"	1 <i>7</i> "	470	53	
	DLS40125	1-1/4"	30	±2"	19"	361	66	
	DLS40150	1-1/2"	40	±2"	20"	329	70	
	DLS40200	2"	50	±2"	22-1/2"	317	78	
	DLS40250	2-1/2"	65	±2"	26"	272	83	
	DLS40300	3"	80	±2"	27-1/2"	201	90	
	DLS40400	4''	100	±2"	30-1/2"	142	120	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSUURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

NSF 372 - LEAD FREE

The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.



SWEAT END DOG LEG, ± 2 " MOVEMENT

DRAWN BY: RI	DAHYA	DATE: 11/20/2020		
APPROVED:		DATE:		
SCALE: N/A	DRAWING NUMB	RAWING NUMBER: DL\$4		