


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PSI*	MAX. SATURATED STEAM PRESSURE (PSI)	SPRING FORCE
		INCH	MM			SINGLE BRAID		
	DLT40050	1/2"	15	±2"	15-1/2"	1075	300	45
	DLT40075	3/4"	20	±2"	16"	792	300	47
	DLT40100	1"	25	±2"	17-1/2"	571	300	53
	DLT40125	1-1/4"	30	±2"	18-1/2"	531	300	66
	DLT40150	1-1/2"	40	±2"	20"	472	300	70
	DLT40200	2"	50	±2"	22"	500	300	78
	DLT40250	2-1/2"	65	±2"	25-1/2"	387	300	83
	DLT40300	3"	80	±2"	27"	288	216	90
	DLT40400	4"	100	±2"	30-1/2"	232	186	120

\*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

**NSF 372 - LEAD FREE**

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>MODEL DLT4</b> THREADED DOG LEG, ±2" MOVEMENT	
DRAWN BY: <b>RDAHYA</b>	DATE: <b>11/20/2020</b>
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: <b>DLT4</b>