


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PRESSURE RATING	SPRING FORCE
		INCH	MM				
	DLW40050	1/2"	15	±2"	15-1/2"	1075	45
	DLW40075	3/4"	20	±2"	16"	792	47
	DLW40100	1"	25	±2"	17-1/2"	571	53
	DLW40125	1-1/4"	30	±2"	18-1/2"	531	66
	DLW40150	1-1/2"	40	±2"	20"	472	70
	DLW40200	2"	50	±2"	22"	500	78
	DLW40250	2-1/2"	65	±2"	25-1/2"	387	83
	DLW40300	3"	80	±2"	27"	288	90
	DLW40400	4"	100	±2"	30-1/2"	232	120
	DLW40500	5"	125	±2"	34"	191	186
	DLW40600	6"	150	±2"	37-1/2"	165	202
	DLW40800	8"	200	±2"	43-1/2"	212	260
	DLW41000	10"	250	±2"	49"	175	383
	DLW41200	12"	300	±2"	54-1/2"	160	390

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL DLW4 WELDED END DOG LEG, ±2" MOVEMENT	
DRAWN BY: RDAHYA	DATE: 11/20/2020
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: DLW4