

							
	I						I
	- A						
	CORRUGATED HOSE & BRAID						
	300 SERIES STAINLESS STEEL						
	ų						
SCH. 40 CARBON STEEL							
	BRAID COLLAR BEVELED FOR WELDING						
Note: Do not use wrenches on hose or braid collar.							
Qty	Model	Size I.D.	A (in)	Pressure @	Weight	Projec	ct Info
		(in)		70°F (PSI)	(Lbs)		
	GASCW0050	1/2	16-7/8	150	0.8		
	GASCW0075	3/4	18-3/8	150	1.4		
	GASCW0100 GASCW0125	1-1/4	19-3/8 19-3/8	150 150	1.8 2.3		
	GASCW0125 GASCW0150			150	2.3		
	GASCW0150 GASCW0200	1-1/2 2	20-1/8 20-7/8	150	3.9		
	GASCW0200 GASCW0250	2-1/2	20-778	150	5.7		
	GASCW0230 GASCW0300	3	25-5/8	150	8.1		
	GASCW0300	4	30-1/4	150	11.9		
MAX INTERMITTENT OFFSET FROM CENTERLINE: 2"							
CONTACT METRAFLEX FOR CUSTOM LENGTHS.							
NSF 372 - LEAD FREE							
The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material							
of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where							
applicable, requiring reduced lead content.							
					REV. 4		
RI						OFFSET UPDATED	DATE 10/26/2016 2323 W. HUBBARD ST.
for pipes in motion tor pipes in motion Tel: 312-738-0415 WWW.METRAFLEX.COM							
CUSTOMER: MODEL G							

PROJECT:

ENGINEER:__

