

METRAFLEX model HP

EXPANSION COMPENSATORS

handle 150 psi-750°F . . . with straight-line travel action of 2 inch Compression . . . 1/2-inch Expansion

ABSORB PIPE MOVEMENT
END EXPANSION NOISE

FOR BOTH VERTICAL AND HORIZONTAL INSTALLATION

Design . . . MetraFlex HP (high pressure) Units with pressure external to bellows are compact to save space and eliminate pipe "networks." Tandem bellows allow center "anti-squirm" ring . . . bellows head is slotted to ride on double "anti-torque rails." Simplicity of design with precision-fitted parts eliminates packing . . . requires no maintenance . . . assures long-life dependability.


Construction . . . All-metal. Stainless Steel Bellows, High quality carbon steel housings and fittings. Welded construction throughout . . . with travelling nipple tackwelded with clip to insure proper installation.

Ends ... Male thread (as shown above). Also available with Weld or flanged ends. Model HPMF is available with SS housing and copper sweat ends for installation in copper lines.

Sizes. . . Standard pipe sizes from 3/4" to 4". See tables at right for specifications.

Operating Limits . . . MetraFlex HP Compensators are tested to a pressure of 225 psi for the recommended

maximum operating pressure of 150 psi. Maximum temperature: 750°F. Further data is posted below in the table of sizes . . . schematic of compensator identifies dimensions specified.



All Sizes and Dimensions in INCHES

Pipe Size	A*	В	С
3/4	123/4	2 ¾	1.050
1	131/4	21/2	1.315
11/4	131/4	3	1.660
11/2	145/8	31/2	1.900
2	145/8	4	2.375
21/2	16	5	2.875
3	16	5%16	3.500
4	163/8	65/8	4.50

The METRAFLEX Co. 2323 WEST HUBBARD STREET • CHICAGO, ILLINOIS 60612
PHONE: (312) 738-3800 http://www.metraflex.com

Products plus ENGINEERING SERVICE in Heating • Piping • Air Conditioning • Plumbing • Refrigeration