

ITEM	PART NAME	MATERIAL
1	BODY	BRONZE ASTM B584 ALLOY C84400
2	STEM	STAINLESS STEEL ASTM 582 ALLOY C30300
3	SPRING	STAINLESS STEEL TYPE 316
4	DISC HOLDER	STAINLESS STEEL TYPE 301
5	DISC	TEFLON
6	SEAT SCREW	STAINLESS STEEL ASTM A276
7	BODY END	BRONZE ASTM B584 ALLOY C84400

DESIGN SPECIFICATIONS:
 Maximum Temperature: 250°F
 Maximum Pressure:
 Saturated Steam - 125 PSI
 Non-Shock W.O.G. - 250 PSI


Qty.	Part Number	Size (in)	A (in)	B (in)	Weight (Lbs)	Project Info
	BSN0050	1/2	2-1/16	1-3/8	0.36	
	BSN0075	3/4	2-1/4	1-5/8	0.48	
	BSN0100	1	2-5/8	2	0.77	
	BSN0125	1-1/4	2-15/16	2-3/8	1.14	
	BSN0150	1-1/2	3-5/16	2-3/4	1.63	
	BSN0200	2	3-11/16	3-3/8	2.27	

NOTE:
 Valve is designed for liquid service only. Install 3 to 4 pipe diameters downstream from pump discharge or elbow to avoid flow turbulence.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<h2>MODEL BSN</h2> <p>SCREWED-END BRONZE CHECK VALVE</p>	
DRAWN BY: DKISH	DATE: 8/28/2013
APPROVED: JC	DATE: 8/28/2013
SCALE: NONE	DRAWING NUMBER: BSN