MODEL SDFL SUCTION DIFFUSER FLEX WITH 150# PLATE FLANGES DESIGNED TO BE INSTALLED IMMEDIATELY UP-STREAM OF A LONG RADIUS 90° ELBOW

A ± 1/8" CARBON STEEL FLANGE 150# DRILLING, FLAT FACE CORRUGATED HOSE & BRAID 300 SERIES STAINLESS STEEL SDF VANE 300 SERIES STAINLESS STEEL								
QTY	PART NUMBER	PIPES		А	PRESSURE	WEIGHT	PROJECT INFORMATION	
		INCH 2"	MM 50	9"	RATING (PSI)*	(LBS)		
├ ──┼	SDFL0200 SDFL0250	2-1/2"	50 65	<u> </u>	516 387	10 15		
	SDFL0230	3"	80 80	9 9''	316	15		
	SDFL0300 SDFL0400	3 4"	100	<u> </u>	232	21		
	SDFL0400 SDFL0500	<u> </u>		<u> </u>	191	21		
		5 6"	125	11		32		
	SDFL0600	6 8''	150 200	11	165 234	32 56		
	SDFL0800 SDFL1000	<u> </u>	200	12	234			
	SDFL1000	10	300	13	161	110		
	SDFL1200	12	350	14	150	110		
MULTIPL TIMES TH REQUIRE	FE WORKING PR Y THE PRESSURE E CORRECTION D TEMPERATURE	RESSURE ABO SHOWN AT FACTOR O E.	OVE 70°F, 70°F F THE	14	MAX	INTERMITTEN	NT OFFSET FROM CENTERLINE 1/8" NT OFFSET FROM CENTERLINE 3/8"	
TEMPERATURE (°F)		FACTOR			NSF 372 - LEAD FREE The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.			
70		1.0						
200		.91		_				
300		.85						
400		.78		_				
500		.77						
600 .76								
					REV.	1 TEMP FA	ACTOR UPDATED DATE 1/4/2017	
					for pip	etra es in motion	2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
CUST	OMER:					MODEL SDFL		
PROJECT:					DRAWN	SDF WITH 150# PLATE FLANGES FOR LR ELBOWDRAWN BY:DATE:11/22/2013		
	NEER:			APPROV	APPROVED: JC DATE: 11/22/2013 SCALE: DRAWING NUMBER: SDFL-1			