
MODEL SDFL90GF SUCTION DIFFUSER FLEX WITH GROOVE x 150# PLATE FLANGE AND A LR ELBOW



QTY	PART NUMBER	PIPE S INCH	SIZE MM	Α	В	PRESSURE RATING (PSI)*	WEIGHT (LBS)	PROJECT INFORMATION
	SDFL90GF0200	2"	50	14-1/4"	3-1/4"	516	13	
	SDFL90GF0250	2-1/2"	65	15"	4''	387	19	
	SDFL90GF0300	3"	80	15-3/4"	4-3/4"	316	22	
	SDFL90GF0400	4"	100	17-1/4"	6-1/4"	232	31	
	SDFL90GF0500	5"	125	20-3/4"	7-3/4"	191	43	
	SDFL90GF0600	6"	150	22-1/4"	9-1/4"	165	56	
	SDFL90GF0800	8"	200	26-3/4"	12-1/4"	234	104	
	SDFL90GF1000	10"	250	30-3/4"	15-1/4"	230	163	
	SDFL90GF1200	12"	300	34-3/4"	18-1/4"	161	233	
	SDFL90GF1400	14"	350	37-3/4"	21-1/4"	150	275	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR				
70	1.0				
200	.91				
300	.85				
400	.78				
500	.77				
600	.76				

PROJECT:_____

ENGINEER:_____

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8" MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	1	TEMP FA	CTOR UPDATE	ED .	DATE	1/4/2017
for pipe	es in	ro motion	flex.	CHICA TEL: 31 FAX: 3	AGO, IL 2-738-3 12-738-	3800

MODEL SDFL90GF

SDF, 150# PLATE FLANGE x GROOVE, LR ELBOW

DRAWN BY: D	KISH	DATE:	11/22/2013
APPROVED: J (DATE:	11/22/2013
SCALE:	DRAWING NUMB		90GF-1