
## MODEL SDFS90 SUCTION DIFFUSER FLEX WITH 150# PLATE FLANGES AND A SR ELBOW



QTY	PART NUMBER	PIPE :	SIZE MM	Α	В	PRESSURE RATING (PSI)*	WEIGHT (LBS)	PROJECT INFORMATION
	SDFS900200	2"	50	10-1/2"	2-1/4"	516	12	
	SDFS900250	2-1/2"	65	11"	2-3/4"	387	18	
	SDFS900300	3"	80	11-1/2"	3-1/4"	316	20	
	SDFS900400	4''	100	12-1/2"	4-1/4"	232	28	
	SDFS900500	5"	125	15-1/2"	5-1/4"	191	38	
	SDFS900600	6"	150	16-1/2"	6-1/4"	165	49	
	SDFS900800	8"	200	19-1/4"	8-1/4"	234	89	
	SDFS901000	10"	250	22-1/4"	10-1/4"	230	136	
	SDFS901200	12"	300	25-1/4"	12-1/4"	161	190	
	SDFS901400	14"	350	27-1/4"	14-1/4"	150	224	

\*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

112 00 112 12 12 13 13 13 13 13 13 13 13 13 13 13 13 13					
TEMPERATURE (°F)	FACTOR				
70	1.0				
200	.91				
300	.85				
400	.78				
500	.77				
600	.76				

CUSTOMER:\_\_\_\_\_\_PROJECT:\_\_\_\_\_

ENGINEER:\_\_\_\_\_

MAX INTERMITTENT OFFSET FROM CENTERLINE 1/8" MAX PERMANENT OFFSET FROM CENTERLINE 3/8"

## NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	1	TEMP FA	CTOR UPDATE	D DA	TE 1/4/2017	
for pip	es in	ra motion	Tex.	CHICAGO TEL: 312-73 FAX: 312-7	38-3800	
MODEL CDECOO						

## **MODEL SDFS90**

SDF WITH 150# PLATE FLANGES AND A SR ELBOW

DRAWN BY: <b>D</b> I	KISH	DATE:	11/22/2013	
APPROVED: JC		DATE:	11/22/2013	
	DRAWING NUMBER:			
N/A		SDFS90-1		