


MATERIAL:
 BELLOWS - MULTI-PLY STAINLESS STEEL
 HOSE AND BRAID - STAINLESS STEEL
 OTHER PARTS - CARBON STEEL

Qty.	Part Number	Size (in)	A (in)	B (in)	C (in)	Effective Area (in ²)	Spring Rate (lb/in)
	GIL04F0200	2	60-3/4	5-1/2	6-1/2	13.2	92
	GIL04F0250	2-1/2	58-7/8	5-1/2	7-1/2	13.2	92
	GIL04F0300	3	64-3/4	6-1/2	7-1/2	20.8	172
	GIL04F0400	4	64-1/2	8-1/2	9-1/2	36.0	103
	GIL04F0500	5	68-7/8	10-3/4	9-1/2	46.4	120
	GIL04F0600	6	76-3/4	12-3/4	11-3/4	58.9	138
	GIL04F0800	8	80-7/8	14	13-3/4	88.8	166

DESIGN DATA:

TEMP. 700°F. (370°C.)
 PRESS. 150 PSI (1034 KPa)
 TEST PRESS. 225 PSI (1551 KPa)

MOVEMENT 4" (100mm) ALL DIRECTIONS



*NOTE: ANCHOR LOADS=
 (MAX PSI X EFFECTIVE AREA)+
 (SPRING RATE X 8)

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content. Not suitable for potable water systems due to materials of construction.

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL GIL04F SEISMIC GATOR WITH FLANGED ENDS +/- 4" MOVEMENT ALL DIRECTIONS	
DRAWN BY: DTH	DATE: 11/18/2014
APPROVED:	DATE:
SCALE: NONE	DRAWING NUMBER: GIL04F