



LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

ITEM	PART NAME	MATERIAL	ASTM NO.
1	BODY	CAST IRON	ASTM A48
2	SEAT	STAINLESS	T304
3	PLUG	STAINLESS	T304
4	SPRING	STAINLESS	T304
5	BUSHING	STAINLESS	T304
6	SCREW	STAINLESS	T304

Notes:

Valve is designed for liquid service only. Install 5 to 10 pipe diameters downstream from pump discharge or elbows to avoid flow turbulence. Valve is designed to be mated to ANSI B16.5 steel flanges.

Valve complies with MSS-SP-125-2010.

ANSI CLASS 125 & 250								
Qty.	Part Number	Size I.D. (in)	A (in)	B (in)	Cv*	Weight (Lbs)	Pressure (PSI)	Project Info
	CVOSSFM702	2	4-1/4	2-5/8	66	6	175	
	CVOSSFM7025	2-1/2	5	2-7/8	88	8	175	
	CVOSSFM703	3	5-3/4	3-1/8	130	11	175	
	CVOSSFM704	4	7	4	228	18	175	
	CVOSSFM705	5	8-3/8	4-3/4	350	28	175	
	CVOSSFM706	6	9-3/4	5-1/2	520	43	175	
ANSI CLASS 125 ONLY								
	CVOSSFM708	8	13-3/8	6-1/2	900	86	175	
	CVOSSFM710	10	16	8-1/4	1450	133	175	
ANSI CLASS 250 ONLY								
	CVOSSFM758	8	13-3/8	6-1/2	900	88	175	
	CVOSSFM760	10	16	8-1/4	1450	137	175	

*Cv is the number of U.S. gallons/minute of 60°F water that will flow through a valve with 1 PSI of pressure drop across the valve.



FOR ADDITIONAL FLOW STRAIGHTENING
SEE THE VANE FLEX AT
www.metroflex.com/vaneflex

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

2	PRESSURE UPDATED	12/9/2013
REV. 1	DRAWING REVISED	DATE 10/11/2013

Metroflex
for pipes in motion

2323 W. HUBBARD ST.
CHICAGO, IL 60612
TEL: 312-738-3800
FAX: 312-738-0415
WWW.METRAFLEX.COM

MODEL CVO700-SS-FM

WAFER STYLE SILENT CHECK VALVE W/ SS TRIM - FM APPROVED

DRAWN BY: **DKISH** DATE: **8/27/2013**
APPROVED: **JC** DATE: **8/27/2013**

SCALE: **NONE** DRAWING NUMBER: **CVO700-SS-FM**