

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN *MUST* HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

QTY	SIZE	MODEL	MOVEMENT	А	В	PSI @ 70° F	WT (LBS)	PROJECT INFO
	2'' (50mm)	VLG40200	+/- 2"	31.375"	11.25"	516	9	
	2.5" (65mm)	VLG40250	+/- 2"	36.625"	13.375"	387	15	
	3'' (80mm)	VLG40300	+/- 2"	39.25"	14.5"	316	20	
	4'' (100mm)	VLG40400	+/- 2"	45"	16.75"	232	32	
	5" (125mm)	VLG40500	+/- 2"	50.5"	18.875"	191	51	
	6'' (150mm)	VLG40600	+/- 2"	56.375"	21"	165	76	
	8'' (200mm)	VLG40800	+/- 2"	68.125"	24.375"	234	144	
	10'' (250mm)	VLG41000	+/- 2"	79.25"	28.5"	230	238	
	12'' (300mm)	VLG41200	+/- 2"	90.25"	32.5"	161	337	

## NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER:\_\_\_\_\_

PROJECT:\_

ENGINEER:\_\_\_\_\_

