

MATERIALS OF CONSTRUCTION

END FITTINGS - CARBON STEEL - SCH 40/STD WT
 HOSE & BRAID - STAINLESS STEEL - 300 SERIES
 ELBOWS - CARBON STEEL - SCH 40/STD WT

NOTE: V-LOOPS 2" AND LARGER INSTALLED IN ANY ORIENTATION OTHER THAN HANGING DOWN MUST HAVE THE 180° RETURN SUPPORTED. (SEE INSTALLATION INSTRUCTIONS.)

CONTACT FACTORY FOR ADDITIONAL SIZES AND MOVEMENTS. ALL DIMENSIONS IN INCHES.

| QTY | SIZE | MODEL | MOVEMENT | A | B | PSI @ 70° F | WT (LBS) | PROJECT INFO |
|-----|-------------|----------|----------|---------|---------|-------------|----------|--------------|
| | 2" (50mm) | VLG80200 | +/- 4" | 37.25" | 14.25" | 516 | 10 | |
| | 2.5" (65mm) | VLG80250 | +/- 4" | 43.5" | 16.875" | 387 | 16 | |
| | 3" (80mm) | VLG80300 | +/- 4" | 46.5" | 18.125" | 316 | 22 | |
| | 4" (100mm) | VLG80400 | +/- 4" | 52.875" | 20.75" | 232 | 35 | |
| | 5" (125mm) | VLG80500 | +/- 4" | 59" | 23.125" | 191 | 54 | |
| | 6" (150mm) | VLG80600 | +/- 4" | 65.5" | 25.625" | 165 | 81 | |
| | 8" (200mm) | VLG80800 | +/- 4" | 77.625" | 29.125" | 234 | 155 | |
| | 10" (250mm) | VLG81000 | +/- 4" | 90" | 33.875" | 230 | 254 | |
| | 12" (300mm) | VLG81200 | +/- 4" | 102" | 38.375" | 161 | 357 | |


NSF 372 - LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

| | |
|--|-----------------------------|
| REV. | DATE |
|  | |
| 2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 WWW.METRAFLEX.COM | |
| METRAFLEX V-LOOP GROOVED ENDS, +/- 4" MOVEMENT | |
| DRAWN BY: SMARTEN | DATE: 7/29/2015 |
| APPROVED: DKISH | DATE: 8/3/2015 |
| SCALE: NONE | DRAWING NUMBER: VLG8 |