


QTY	PART NUMBER	PIPE SIZE		MOVEMENT	CENTER TO END	PSI*	MAX. SATURATED STEAM PRESSURE (PSI)	SPRING FORCE
		INCH	MM			SINGLE BRAID		
	DLT40050	1/2"	15	±2"	15-1/2"	1075	300	45
	DLT40075	3/4"	20	±2"	16"	792	300	47
	DLT40100	1"	25	±2"	17-1/2"	571	300	53
	DLT40125	1-1/4"	30	±2"	18-1/2"	531	300	66
	DLT40150	1-1/2"	40	±2"	20"	472	300	70
	DLT40200	2"	50	±2"	22"	500	300	78
	DLT40250	2-1/2"	65	±2"	25-1/2"	387	300	83
	DLT40300	3"	80	±2"	27"	288	216	90
	DLT40400	4"	100	±2"	30-1/2"	232	186	120

\*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE.

TEMPERATURE (°F)	FACTOR
70	1.0
200	0.91
300	0.85
400	0.78
500	0.77
600	0.76

**NSF 372 - LEAD FREE**

The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
<b>MODEL DLT4</b> THREADED DOG LEG, ±2" MOVEMENT	
DRAWN BY: <b>RDAHYA</b>	DATE: <b>11/20/2020</b>
APPROVED:	DATE:
SCALE: N/A	DRAWING NUMBER: <b>DLT4</b>