



STANDARD SCREENS

Service	Sizes (in)	Perf. (in)
Steam	2 - 6	.045
	8 - 16	.062
Liquid	2 - 3	.045
	4 - 16	.125

Qty	Part Number	Size I.D. (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Port Size		Blowoff Size (in)	Weight (in)
								1 & 2 (in)	3 (in)		
	TFC20200	2	9-7/8	6-3/16	2-1/2	5	2-1/2	1/2	1	1/2	33
	TFC20250	2-1/2	11-1/4	7-5/8	3	5	3	1/2	1	1	49
	TFC20300	3	12-1/2	8-1/4	3	6	3	1/2	1	1	57
	TFC20400	4	14-7/8	10-1/16	3	7	3	1/2	1	1-1/4	108
	TFC20500	5	17-15/16	12-1/2	3-1/2	9	3-1/2	1/2	1	1-1/4	157
	TFC20600	6	20-3/8	14-5/16	4	10	4	1/2	1	1-1/2	215
	TFC20800	8	24	17-3/8	4	12	4	1/2	1	1-1/2	316
	TFC21000	10	29-1/2	20-7/8	5	15	5	1/2	1	2	525
	TFC21200	12	33-3/4	23-9/16	5	17	5	1/2	1	2	704
	TFC21400	14	37-1/4	27-13/16	6	19	6	1/2	1	2	906
	TFC21600	16	42-3/8	29-1/2	6	21	6	1/2	1	2-1/2	1336

LEAD FREE

The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards, where applicable, requiring reduced lead content.

OPERATING TEMPERATURE AND PRESSURE:

Steam..... 250 psi at 400 °F
 Water, Oil, Gas..... 400 psi at 150 °F

PROJECT INFO

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL TF2 Y-TYPE 250# FLANGED STRAINER	
DRAWN BY: DKISH	DATE: 12/27/2013
APPROVED: JC	DATE: 12/27/2013
SCALE: NONE	DRAWING NUMBER: TF2