


MODEL LPDTMAG0150
LOW PRESSURE DROP
THREADED STRAINER
WITH MAGNETIC INSERT



PRODUCT CAN BE ROTATED 90° AXIALLY TO PROVIDE MAINTENANCE CLEARANCE

MATERIALS OF CONSTRUCTION

BODY, COVER PLATE - 304 STAINLESS STEEL
SCREEN - 304 STAINLESS STEEL
O-RING GASKET - EPDM
DRYWELL-304 STAINLESS STEEL
MAGNETS-NEODYMIUM

STANDARD SCREENS

SERVICE	SIZE	PERF
LIQUID	1-1/2"	.045"

OPERATING TEMPERATURE/PRESSURE

WATER, OIL, GAS.....175 PSI @ 150°F
MAXIMUM OPERATING TEMPERATURE: 175°F*
*CONTACT FACTORY FOR CUSTOM OPTIONS
FOR OPERATING TEMPERATURES ABOVE 175°

QTY	PART NUMBER	PIPE SIZE	A	B	SCREEN AREA (in ²)	BLOWOFF SIZE (NPT)	WEIGHT (LBS)
	LPDTMAG0150	1-1/2"	5-5/8"	4"	52.0	3/8"	6.5

CUSTOMER: _____
PROJECT: _____
ENGINEER: _____

REV.		DATE	
		2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL LPDTMAG0150 LPDT MAGNETIC THREADED			
DRAWN BY: RUBENC		DATE: 1/14/2026	
APPROVED:		DATE:	
SCALE: N/A	DRAWING NUMBER: LPDTMAG0150		