

QTY	PART NUMBER	SIZE	OAL	PRESSURE RATING*	PROJECT INFORMATION
	SFM0050	1/2"	13-1/2"	1075 PSI	
	SFM0075	3/4"	15-1/8"	792 PSI	
	SFM0100	1"	15"	571 PSI	
	SFM0150	1-1/2"	16-5/8"	472 PSI	
	SFM0200	2"	18-1/8"	516 PSI	
	SFM0250	2-1/2"	20-3/4"	387 PSI	
	SFM0300	3"	21-5/8"	316 PSI	
	SFM0400	4"	23-3/8"	232 PSI	
	SFM0500	5"	26-1/2"	191 PSI	
	SFM0600	6"	26-3/8"	165 PSI	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE

MAX INTERMITTENT OFFSET FROM CENTERLINE 2"


TEMPERATURE (°F)	FACTOR
70	1.0
200	.91
300	.85
400	.78
500	.77
600	.76

LINING, CUSTOM MOVEMENT AND HIGHER PRESSURE AVAILABLE UPON REQUEST

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL SFM 304 SS TRI-CLAMP FLEXIBLE CONNECTOR	
DRAWN BY: TIMM	DATE: 04/28/2026
APPROVED: JACKSONK	DATE: 04/28/2026
SCALE: N/A	DRAWING NUMBER: SFM