


QTY	PART NUMBER	SIZE	OAL	PRESSURE RATING*	PROJECT INFORMATION
	SFM0050316	1/2"	13-1/2"	1075 PSI	
	SFM0075316	3/4"	15-1/8"	792 PSI	
	SFM0100316	1"	15"	571 PSI	
	SFM0150316	1-1/2"	16-5/8"	472 PSI	
	SFM0200316	2"	18-1/8"	516 PSI	
	SFM0250316	2-1/2"	20-3/4"	387 PSI	
	SFM0300316	3"	21-5/8"	316 PSI	
	SFM0400316	4"	23-3/8"	232 PSI	
	SFM0500316	5"	26-1/2"	191 PSI	
	SFM0600316	6"	26-3/8"	165 PSI	

*FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY THE PRESSURE SHOWN AT 70°F TIMES THE CORRECTION FACTOR OF THE REQUIRED TEMPERATURE

MAX INTERMITTENT OFFSET FROM CENTERLINE 2"

TEMPERATURE (°F)	FACTOR
70	1.0
200	.91
300	.85
400	.78
500	.77
600	.76

LINING, CUSTOM MOVEMENT AND HIGHER PRESSURE AVAILABLE UPON REQUEST

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
MODEL SFM 316 SS TRI-CLAMP FLEXIBLE CONNECTOR	
DRAWN BY: TIMM	DATE: 04/28/2026
APPROVED: JACKSONK	DATE: 04/28/2026
SCALE: N/A	DRAWING NUMBER: SFM316

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____